

E-Dimming LED Driver

Design and Quality EASEIC of USA

LPD-100-30A

E-Dimming 0/1-10V DRIVER

SPEC SHEET



100W 30V 3.35A 0/1-10V Dim
LPD-100-30A
69210001



SELV IP67 RoHS


Features

- Universal AC input (90~305Vac)
- Designed for LED lighting applications
- Built-in 3 in 1 dimming function(0/1-10V,PWM or Resistance)
- IP67/IP65 design for indoor or outdoor installations
- These drivers operate to specification under wide temperature and electrical ranges to ensure reliability
- LPD series LED drivers for use in Class I, Division 2 hazardous location luminaires
- Cooling by free air convection
- Suitable for dry, damp, and wet location
- 5 year warranty

Benefits

- Applies to all indoor and outdoor LED lighting
- Helps to maximize energy savings and allows application specific light levels
- Supports majority of available dimming solutions

Wire Diagram



Note:

Install in accordance with National and Local Electrical Codes.

Please pay special attention to wiring installation guidelines,

Wrong wiring will cause damage to the LED driver.

Before connection the power, make sure you have access to the LED load.

Product Data

Input Voltage (Vac)	Output Power (W)	Output Voltage (V)	Output Current (A)	Efficiency @Max Load and 70°C case	Max Case Temp. (°C)	Input Current (Arms)	Max Input Power (W)	THD @Max Load (%)	Power Factor @Max Load	Weight (Lbs/kgs)	Envir. Protection Rating
120	100	20-30	3.35	90.0	Life-75°C UL-85°C	0.97	116.4	<20%	>0.96	1.8/0.82	UL damp and dry
230				90.0		0.51		<20%			
277				91.0		0.42		<20%			

LPD-100-30A

E-Dimming 0/1-10V DRIVER

SPEC SHEET

Electrical Specifications

Ordering Information			
Type	LPD-100-30A		
Order Code	69210001		
Full product name	E-Dimming 100W 30V 3.35A 0/1-10V Dim		
Input Information			
Line Voltage	100-277Vac_rms		
Line Current	0.97A@120VAC	0.51A@230VAC	0.42A@277VAC
Line Frequency	50/60Hz		
Min, Mains Voltage operational	90[<i>min</i>]		
Max, Mains Voltage operational	305[<i>max</i>]		
THD(total)	<20%		
Power Factor(PF)	>0.96		
Inrush Current(Typ.)	Cold Start 65A(<i>t</i> _{width} =270us measured at 50% <i>I</i> _{peak}) at 230VAC		
Leakage Current(Typ.)	<0.75mA/230VAC		
Output Information			
Output voltage	20V to 30V		
Output Constant Current	3.35A		
Maximum open circuit voltage	<60V		
Output Current Ripple (ripple=peak to peak)	2% of nominal output voltage (whichever is greater),measured at 20Mhz bandwidth with 0.1uf ceramic capacitor in parallel with 10uf electrolytic capacitor connected at the end of the output connector.		
Protections	Over Current, Over Voltage, Short Circuit and Open Circuit Protection for LED+ and LED-		
Ambient Temp Range	-40°C to +70°C, 20-95% RH non-condensing		
Max Case Temperature(Tc)	75°C for Life & 85°C for UL Safety		
Features			
Dimming Interface	0-10V(1-10V) Dimming 10V PWM Signal Dimming Resistance Dimming		
0-10V Dimming Specifications	250uA source current form driver, See dim curve for detail.		
10V PWM Signal	100Hz-3KHz PWM		
Resistance Dimming	100Kohm variable resistance		
Dimming range	10-100%		
Environment & Approbation			
Environmental Protection Rating	UL damp and dry		
Agency Approbations	UL8750,UL1310, CSA-C22.2 No.250.0-08,ENEC EN61347-1,EN61347-2-13 independent, EN62384, TUV EN60950-1		
Electromagnetic Compliance	FCC Title 47 Part 15 Class A Compliance to EN55015,EN61000-3-2 Class C(@100% Load);en6100-3-3 Compliance to EN61000-4-2,3,4,5,6,8,11;EN61547,EN55024, light industry level(surge 2KV), criteria A		
Audible noise	<24dB Class A		

All the specifications are typical and at 25 °C Tcase unless specified otherwise


LPD-100-30A

E-Dimming 0/1-10V DRIVER

SPEC SHEET

Mechanical Specifications

Mechanical Drawing



Dimensions

	In.	mm
Case Length(L)	7.4	189
Case Width(W)	2.6	66
Case Height(H)	1.5	38
Mounting Holes(I1)	6.3	161
Mounting Holes(I2)	1.3	34
Mounting Holes(I3)	0.2	5
Mounting Holes(I4)	6.9	174
Input Wire(Wire1) SJTW 18AWG x 3C	11.8	300 ± 20
Output Wire(Wire2) SJTW 2x18 AWG x 2C	11.8	300 ± 20
Overall Length	7.4	189

EASEIC

© Copyright 2013 EASEIC INC.
All rights reserved. Rev A1.0
Data is subject to change without notice.
www.easeic.com

Easeic Inc.

27 Hall Street, Brooklyn, NY 11205
Tel.: 1-718-243-9388
Fax: 1-718-243-9403
Customer Support
Customer Care: 1-646-4029788
E-Mail: ny@easeic.com

Easeic Asia Limited.

Rm. 19C, Lockhart Ctr., 301-307
Lockhart Rd., Wan Chai, Hong Kong
Tel.: 852-6955-8075
Fax: 852-6915-3639
E-Mail: info@easeic.com

Easeic Sci-tech Co., Ltd.

No. 37 Huancun Xi Rd., Liangtian
Industrial Area,
Baiyuan District, Guangzhou, China
Tel.: 86-20-8230-9676
Fax: 86-20-8230-9677
E-Mail: sales@easeic.com